

# DATASHEET

#### Table saw

## TKS 316 E (400 V)

Mobile DIY machine for trimming boards, for cutting cuts, bevel and angle cuts

#### Article number v 5902317

#### Brand V Holzstar

Availability v In stock

### Immediate delivery

#### Catalog directory v

Woodworking machinery » Circular saw / Sliding table saws » Table Saws

#### Purchase 🗸

Minimum 1 pc(s).



#### Delivery content v

- Chassis
- Sliding table with miter gauge
- Table extension
- Combined parallel and miter fence
- Carbide Blade Ø 315 x 3,6 x Ø 30 mm Z24
- Saw blade guard with suction hose
- Push stick

#### Shipping informations V

| Packaging Metric | cs     | Weights |       | Delivery |          | Other   |     |
|------------------|--------|---------|-------|----------|----------|---------|-----|
| Length           | 890 mm | Gross   | 55 kg | Delivery | Carrier  | DualUse | ×   |
| Width            | 610 mm | Net     | 50 kg | Content  | 1 pc(s). | SCIP    | n/a |
| Height           | 460 mm |         |       |          |          | SVHC    | No  |

#### Root data 🗸

| Country of origin | EAN           | Custom number | Quantity unit |
|-------------------|---------------|---------------|---------------|
| * China           | 4036351260363 | 84659120      | pc(s).        |

#### Description ~


- Inclination of the saw blade from 0 to 45°, adjustable without tools
- Height adjustment of the saw blade via hand crank and scale
- Large aluminum rip fence with eccentric quick release, can be used as a miter fence as well
- Large, galvanized steel machine table
- Easy to move thanks to integrated chassis with two wheels and foldable transport handles
- Delivered unmounted

#### Media informations v



Simple manual height adjustment of the saw unit via hand crank, tilt adjustment from 0 – 45  $^\circ$ 

Ball-bearing sliding carriage with miter fence, infinitely adjustable from 0 to 45° with quick clamping lever



Easy and precise adjustment of the rip fence with eccentric quick tension by scale



Conveniently movable by chassis and folding transport handles

#### Technical data 🗸

| Dimensions and weights            |                        |   |           |
|-----------------------------------|------------------------|---|-----------|
| Length (product) approx.          | 1600 mm                | Width/depth (product) approx.                 | 600 mm    |
| Height (product) approx.          | 1050 mm                | Net weight approx.                            | 55 kg     |
| Extraction port                   |                        |   |           |
| Extraction port diameter bottom   | 100 mm                 | Saw blade protection extraction port diameter | 35 mm     |
| Electrical Data                   |                        |   |           |
| Supply voltage                    | 400 V                  | Mains frequency                               | 50 Hz     |
| Absorbed power drive motor        | 2,8 kW                 | Delivery power                                | 2,2 kW    |
| Protection class drive motor      | IP 54                  | Duty type drive motor                         | S6 40%    |
| Motor speed                       | 2800 min <sup>-1</sup> | Total current draw                            | 4.7 A     |
| Sliding carriage and table        |                        |   |           |
| Table length                      | 800 mm                 | Table width                                   | 550 mm    |
| Work height                       | 850 mm                 |   |           |
| Circular saw unit                 |                        |   |           |
| Max. cutting width with rip fence | 290 mm                 | Saw blade angle                               | 90 – 45 ° |
| Max. cutting height 90°           | 83 mm                  | n Max. cutting height 45°                     |           |
| (Main) saw blade diameter         | 315 mm                 | (Main) saw blade speed 2800 mi                |           |

#### Accessories 🗸

| Cut-to-size alte<br>blade<br>KSB-WZ 315/2<br>Highest quality level<br>stationary machines |  |   |                      |
|---|--|---|----------------------|
| Article number ∨<br>5263128   | Availability V<br>In stock<br>Immediate delivery | <b>Purchase                                    </b> | Price informations V |

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.