

Sliding table saw

FKS 255-1300 (400V)

Robust and precise design with swivel saw blade



Article number ▼

5902036

Brand ▼

Holzstar

Availability ▼

In stock

Immediate delivery

Catalog directory ▼

Woodworking machinery » Circular saw /
Sliding table saws » Sliding table saws »
FKS



Purchase ▼

Minimum 1 pc(s).


Delivery content ▼

- Trimming shoe
- Eccentric tensioner
- Angular stop -45° to 45°
- Circular saw blade 254 x 30 x 3.0 mm Z40

Shipping informations ▼

Packaging Metrics		Weights		Delivery		Other	
Length	820 mm	Gross	185 kg	Delivery	Carrier	DualUse	✘
Width	770 mm	Net	150 kg	Content	1 pc(s).	SCIP	n/a
Height	945 mm					SVHC	No

Root data ▼

Country of origin	EAN	Custom number	Quantity unit
 China	4036351279426	84659120	pc(s).

Description ▼

- Heavy grey cast iron work table for low-vibration work and precise, straight cuts
- Saw unit can be swivelled up to 45 degrees, adjustment via handwheel
- Cutting plane directly on the saw blade
- Table boom with extendable telescopic stop and two folding stops for plates and large workpieces
- Telescopic stop swivelling by 45 degrees on both sides
- Aluminum parallel stop on round rod guide with fine adjustment
- Standard table widening and extension allow easy work with larger workpieces
- Large central suction connection with 100 mm diameter

Media informations





Saw blade height and swivel conveniently adjustable via handwheels



Telescopic stop with a length of 1100 to 1900 mm

Technical data ▼

Dimensions and weights			
Length (product) approx.	1320 mm	Width/depth (product) approx.	1750 mm
Height (product) approx.	1120 mm	Net weight approx.	155 kg
Extraction port			
Extraction port diameter bottom	100 mm	Saw blade protection extraction port diameter	30 mm
Electrical Data			
Supply voltage	400 V	Mains frequency	50 Hz
Absorbed power drive motor	2.0 kW	Delivery power	1,5 kW
Total rated value	3.5 A	Motor speed	2800 min ⁻¹
Sliding carriage and table			
Trimming frame length	600 mm	Trimming frame width	460 mm
Sliding carriage length	1320 mm	Sliding carriage width	238 mm
Table length	790 mm	Table width	350 mm
Work height	835 mm		
Noise emission			
Sound pressure level	83.7 dB(A)		
Circular saw unit			
Max. cutting width with rip fence	610 mm	Max. cross cut width left from saw blade	845 mm
Trimming length	1250 mm	Saw blade angle	90 – 45 °
Max. cutting height 90°	80 mm	Max. cutting height 45°	54 mm
(Main) saw blade diameter	254 mm	(Main) saw blade speed	4000 min ⁻¹


Equipment ▼


Handle for sliding carriage	✓	Saw rip fence	with round rod guide
Table broadening	✓	Table lengthening	✓
Saw blade cover	✓		


Accessories



Saw blade 254 x 30 x 3 mm Z40

Article number 
5912026


Availability 
In stock
Immediate delivery


Purchase 
Minimum 1 pc(s).


Price informations 



Mitre fence FKS 255 and TF170E

Article number 
5912027

Availability 
No stock available
Information:
Next availability
Unknown

Purchase 
Minimum 1 pc(s).

Price informations 



Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.